

## ***FAST WATER BUOY TYPE IFWB760***

### **DATASHEET**

The buoy IFWB760 is special designed to be a stable aid to navigation in waters with a 2 - 6 knots current.

The buoy has features to accommodate an selfcontained beacon, if required an integrated radar reflector can be incorporated as an option.

Rotational moulded in self coloured polyethylene in cone or can configuration, and foam filled with polystyrene EPS the buoy is nearly unsinkable.

Internal bracing is provided for easy handling.



<b>Application</b>	<b>: Rivers, lakes, canals, harbours.</b>
<b>Type</b>	<b>: IFWB 760</b>
<b>Make</b>	<b>: I.T.O. Vaarwegmarkering BV.</b>
<b>Material/type</b>	<b>: Polyethylene, self colored U.V. stabilized polystyrene filled.</b>
<b>Foam-Fill Material</b>	<b>: Expanded Polystyrene Foam EPS</b>
<b>Material thickness</b>	<b>: Min. 6 mm.</b>
<b>Diameter</b>	<b>: 760 mm.</b>
<b>Length</b>	<b>: 1805 mm. (including counterweight).</b>
<b>Fabrication process</b>	<b>: Rotational moulding.</b>
<b>Bracing</b>	<b>: Internal.</b>
<b>Radar reflector</b>	<b>: Optional.</b>
<b>Water depth</b>	<b>: up to 20 meters.</b>
<b>Lantern mounting</b>	<b>: 4 inserts M 8 on a 200 mm pitch circle.</b>
<b>Weight</b>	<b>: Appr. 48 kg.</b>

**I.T.O. Vaarwegmarkering BV**  
**'s Gravendijkseweg 23 2201 CZ**

**Noordwijk Holland**

**E-mail [info@itonavaids.com](mailto:info@itonavaids.com)**

**DOC.NO: IFWB760 rev1**

**tel. +31 71 3611987**

**fax. +31 71 3614219**

**[www.itonavaids.com](http://www.itonavaids.com)**

